Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: **B** 

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model: Serial number: NIVIUK

PG\_1835.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 16

TOYOK416V1

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	70	Range of speed system (cm)	10
Minimum weight in flight (kg)	45	Speed range using brakes (km/h)	14
Glider's weight (kg)	1.8	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	14.35		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	40		

12 13 14 19 20 21 22 23 15

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: **C** 

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:



PG\_1835.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 16

TOYOK416V1

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	90	Range of speed system (cm)	10
Minimum weight in flight (kg)	45	Speed range using brakes (km/h)	14
Glider's weight (kg)	1.8	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	14.35		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model: Serial number: CONTRACT
INTERPRETABLE

PG\_1857.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 18

KODE181

# Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	70	Range of speed system (cm)	10
Minimum weight in flight (kg)	50	Speed range using brakes (km/h)	14
Glider's weight (kg)	2	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	16.05		
Hamman and for tooking (many might)		Incorpositions (cubishouse because first)	
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Flugsau	Warning! Before use refer to user's manual	
Harness model	X-Light M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	40		
Distance between risers (cm)	40		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: **B** 

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG\_1857.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 18

KODE181

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	80	Range of speed system (cm)	10
Minimum weight in flight (kg)	50	Speed range using brakes (km/h)	14
Glider's weight (kg)	2	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	16.05		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: **C** 

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Serial number:

Model:

CONTRACT
INTERPRETATION

PG\_1857.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 18

KODE181

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	100	Range of speed system (cm)	10
Minimum weight in flight (kg)	50	Speed range using brakes (km/h)	14
Glider's weight (kg)	2	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	16.05		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Flugsau	Warning! Before use refer to user's manual	
Harness model	X-Light M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	40		
Distance between risers (cm)	46		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG\_1832.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 20

**KODE2011** 

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	85	Range of speed system (cm)	13
Minimum weight in flight (kg)	60	Speed range using brakes (km/h)	14
Glider's weight (kg)	2.2	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	17.61		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:



PG\_1772.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 22

TOYOK422V1

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	90	Range of speed system (cm)	13
Minimum weight in flight (kg)	65	Speed range using brakes (km/h)	14
Glider's weight (kg)	2.3	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	19.37		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	every 100 hours of use or every 24 months	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Altiplume M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG\_1822.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 24

TOYOK424V1

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	95	Range of speed system (cm)	13
Minimum weight in flight (kg)	70	Speed range using brakes (km/h)	14
Glider's weight (kg)	2.6	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	21.13		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Supair	Warning! Before use refer to user's manual	
Harness model	Evo XC 3 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	44		

Route du Pré-au-Comte 8 \* CH-1844 Villeneuve \* +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



Classification: A

In accordance with standards EN 926-1:2015, EN 926-2:2013 and NfL 2-565-20:

Date of issue (DMY):

Manufacturer:

Model:

Serial number:

CONTRACT

PG\_1823.2021

01.09.2021

Niviuk Gliders / Air Games S.L.

Kode P 26

KODE126

## Configuration during flight tests

Paraglider		Accessories	
Maximum weight in flight (kg)	115	Range of speed system (cm)	13
Minimum weight in flight (kg)	90	Speed range using brakes (km/h)	14
Glider's weight (kg)	2.8	Total speed range with accessories (km/h)	24
Number of risers	3	Range of trimmers (cm)	0
Projected area (m2)	23.33		
Harness used for testing (max weight)		Inspections (whichever happens first)	
Harness type	ABS	Every 2 years or every 100 flight hours.	
Harness brand	Advance	Warning! Before use refer to user's manual	
Harness model	Success 4 M	Person or company having presented the glider for testing: <b>None</b>	
Harness to risers distance (cm)	44		
Distance between risers (cm)	48		